



Serving Our Customers Since 1975

# SAFETY DATA SHEET

Issue Date: 30 September 2015

Revision Date: 30 September 2015

Version 1

## 1. PRODUCT AND COMPANY IDENTIFICATION

### Product Identifier

Product Name: **RENEW**

Product Description: **ACOUSTICAL CEILING TILE RESTORER**

### Other Means of Identification

Product # 96715

Synonyms None

### Details of the Supplier of the Safety Data Sheet

Company Name CHEMCO INDUSTRIES, INC.  
5731 Manchester Avenue  
St. Louis, MO 63110  
www.chemcoindustries.com  
314-647-1888  
1-800-854-4236 (to Reorder)

### Emergency Telephone Number

Emergency Telephone INFOTRAC 1-800-535-5053

## 2. HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Aerosol: Category 1

Liquefied Gas

Skin Irritant: Category 2

Eye Irritant: Category 2A

Specific Target Organ Toxicity (Single Exposure): Category 3

Aspiration Hazard: Category 1

**HAZARD STATEMENT(S): DANGER:** Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. This product contains the following percentage of chemicals of unknown toxicity: 14%

**PRECAUTIONARY STATEMENTS:** Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

### **SYMBOL:**



**HAZARDS NOT OTHERWISE CLASSIFIED:** N/A

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Acetone	67-64-1	10-30
Ethyl Alcohol	64-17-5	5-10%
Heptane	142-82-5	10-30%
Isoparaffinic Hydrocarbon	64742-47-8	3-7%
Propane/n-Butane	68476-86-8	15-40%

### 4. FIRST AID MEASURES

**EYES:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**INGESTION:** If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.

**INHALATION:** Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

**SKIN:** If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision  
 Skin: defatting and dermatitis  
 Inhalation: Anesthetic, irritation, Central Nervous System depression  
 Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

**CHRONIC HEALTH HAZARDS:** May be toxic to kidneys and liver.

**NOTE TO PHYSICIAN:** There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

### 5. FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Dry chemical or suitable for surrounding materials.

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray/stream.

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires. Use water spray only to cool exposed containers.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

**HAZARDOUS COMBUSTION PRODUCTS:** Oxides of carbon

### 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PROTECTIVE EQUIPMENT:** Refer to section VIII for proper Personal Protective Equipment.

**SPILL:** Wipe up small spill with towel and allow area to dry. excess may be removed after drying with sandpaper or other scraping device. dispose of residue in accordance with federal, state and local guidelines.

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

## 7. HANDLING AND STORAGE

**HANDLING AND STORAGE:** Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

**OTHER PRECAUTIONS:** Keep out of the reach of children. Follow label directions exactly. Vapors may collect in low lying areas.

**INCOMPATIBILITY:** Some plastics and painted surfaces, pre-test before using.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Acetone	1000 ppm	500 ppm
Ethyl Alcohol	1000 ppm	1000 ppm
Heptane	400 ppm	400 ppm
Isoparaffinic Hydrocarbon	400 ppm	400 ppm
Propane/n-Butane	1000 ppm	1000 ppm

**ENGINEERING CONTROLS / VENTILATION:** Ambient ventilation suitable, forced ventilation should not be required

**RESPIRATORY PROTECTION:** Not required with normal use. Wear NIOSH/MSHA approved respiratory protection if exposure limits are exceeded.

**PERSONAL PROTECTIVE EQUIPMENT:** Safety glasses and chemical resistant gloves

**ADDITIONAL MEASURES:** Wash hands and all equipment thoroughly after use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE:** White Spray

**ODOR:** Hydrocarbon odor

**ODOR THRESHOLD:** N/D

**BOILING POINT:** N/D

**FREEZING POINT:** N/D

**FLAMMABILITY:** Extremely Flammable Aerosol

**FLASH POINT:** N/D

**AUTOIGNITION TEMPERATURE:** N/D

**LOWER FLAMMABILITY LIMIT:** N/D

**UPPER FLAMMABILITY LIMIT:** N/D

**VAPOR PRESSURE (mm Hg):** N/A

**VAPOR DENSITY (AIR=1):** > 2

**EVAPORATION RATE:** > 1

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** 0.87

**pH:** N/A

**SOLIDS (%):** 26%

**SOLUBILITY IN WATER:** 0%

**PARTITION COEFFICIENT: n-OCTANOL/WATER (KOW):** N/D

**VOLATILITY INCLUDING WATER (%):** 80.8%

**VOLATILE ORGANIC COMPOUNDS (VOC):** 51%

**DIELECTRIC STRENGTH (Volts):** N/A

**DECOMPOSITION TEMPERATURE:** N/D

**VISCOSITY:** N/D

## 10. STABILITY AND REACTIVITY

**REACTIVITY:** None Known

**CHEMICAL STABILITY:** Stable

**CONDITIONS TO AVOID:** Temperatures greater than 122°F and sources of ignition.

**INCOMPATIBILITY:** Some plastics and painted surfaces, pre-test before using.

**HAZARDOUS DECOMPOSITION OR BY-PRODUCT:** Oxides of carbon

**POSSIBLE HAZARDOUS REACTIONS:** None Known

## 11. TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL INFORMATION:** **Acetone** (67-64-1) LD50 (Oral, Rat) 5800 mg/kg; LD50 (Oral, Mouse) 3000 mg/kg; LD50 (Oral, Rabbit) 5340 mg/kg; LC50 (Inhalation, Rat, 8hr) 50100 mg/m<sup>3</sup>; LC50 (Inhalation, Mouse, 4hr) 44,000 mg/m<sup>3</sup> **Ethyl Alcohol** (64-17-5) LC50 (Inhalation, Mouse, 4hr) 39 gr/m<sup>3</sup>; LC50 (Inhalation, Rat, 10hr) 20,000 ppm; LD50 (Oral, Mouse) 3450 mg/kg; LD50 (Oral, Rabbit) 6300 mg/kg; LD50 (Oral, Rabbit) 7060 mg/kg **Heptane** (142-82-5) LD50 (Oral, Rat) 15,000 mg/kg; LC50 (Inhalation, Rat, 4hr) 103 g/m<sup>3</sup>; LD50 (Dermal, Rabbit) 2,000 mg/kg **Isoparaffinic Hydrocarbon** (64742-47-8) LD50 (Oral, Rat) 5 g/kg; LD50 (Dermal, Rabbit) 2 g/kg; LC50 (Rat, 4hr) 5 mg/L

**ROUTES OF ENTRY:** Eyes, Ingestion, Inhalation, Skin

**EYES:** Causes irritation, defatting.

**INGESTION:** Causes gastrointestinal irritation, nausea, diarrhea, absorption through gastrointestinal tract may produce symptoms of central nervous system depression ranging from light headedness to unconsciousness.

**INHALATION:** Dizziness, headache, nausea, depression of central nervous system, prolonged exposure may lead to unconsciousness

**SKIN:** Causes localized defatting, irritation, dermatitis.

**MEDICAL CONDITION AGGRAVATED:** Excessive exposure will aggravate pre-existing skin disorders, respiratory, liver, kidney, cardiovascular or pulmonary illnesses.

**ACUTE HEALTH HAZARDS:** Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, and aspiration risk

**CHRONIC HEALTH HAZARDS:** May be toxic to kidneys and liver.

**CARCINOGENICITY:** OSHA: No ACGIH: No NTP: No IARC: No OTHER: N/A

## 12. ECOLOGICAL INFORMATION

**ECOLOGICAL INFORMATION:** **Acetone** (67-64-1) LC50 (Trout, 96hr) 5540 mg/L; LC50 (Bluegill, 96hr) 8300 mg/L; LC50 (Fathead Minnow, 96hr) 7500 mg/L **Isoparaffinic Hydrocarbon** (64742-47-8) Not expected to be harmful or demonstrate chronic toxicity toward aquatic organisms. Expected to be readily biodegradable. Do not contaminate water when disposing of equipment washwaters.

**BIODEGRADABILITY:** Component or components of this product are not biodegradable.

**BIOACCUMULATION:** Components in this mixture can bioaccumulate in aquatic organisms.

**SOIL MOBILITY:** This product is mobile in soil.

**OTHER ECOLOGICAL HAZARDS:** This material is toxic to aquatic life.

### 13. DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** Dispose of in accordance with federal, state, and local regulations. Do not dump in sewers. Wrap container and place in trash collection, do not puncture, incinerate, or reuse container.

**RCRA STATUS:** Waste likely considered Non-hazardous under RCRA, however product should be fully characterized prior to disposal (40 CFR 261). Solvent is flammable please refer to (40 CFR 261).

### 14. TRANSPORT INFORMATION

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**PACKAGING GROUP:** N/A

**AIR SHIPMENT**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**SHIPPING BY WATER:**

**VESSEL (IMO/IMDG)**

**PROPER SHIPPING NAME:** Aerosols, Ltd. Qty.

**HAZARD CLASS/DIVISION:** 2.1

**UN/NA NUMBER:** UN 1950

**ENVIRONMENTAL HAZARDS WATER:** Marine Pollutant

### 15. REGULATORY INFORMATION

**TSCA STATUS:** All Chemicals are listed or exempt.

**CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT):** Acetone (67-64-1) Reportable Quantity = 5,000 lbs

**SARA 311/312 HAZARD CATEGORIES:** Fire Hazard

**SARA 313 REPORTABLE INGREDIENTS:** Ethyl Alcohol (64-17-5) acute, chronic, flammable.

**STATE REGULATIONS:** Acetone (67-64-1) Connecticut hazardous material survey, Illinois toxic substances disclosure to employee act, Illinois chemical safety act, New York release reporting list, **RTK** - RI, PA, FL, MN, MA, NJ; Massachusetts spill list, New Jersey spill list, Louisiana spill reporting, California List of Hazardous Substances (8 CCR 339): Acetone TSCA 8(b) inventory: Acetone TSCA 4(a) final test rules: Acetone TSCA 8(a) IUR: Acetone

**INTERNATIONAL REGULATIONS:** Acetone (67-64-1) Australia, China, Europe (EINECS), Japan, Korea, United Kingdom, Canada, WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects (TOXIC). p. 6; DSCL (EEC): R11- Highly flammable. R36- Irritating to eyes. S9- Keep container in a well-ventilated place. S16- Keep away from ignition sources. S26- In case of eye contact, rinse immediately with plenty of water and seek medical advice.

**NFPA HEALTH:** 2  
**NFPA FLAMMABILITY:** 3  
**NFPA REACTIVITY:** 0  
**NFPA OTHER:** None

**HMIS HEALTH:** 2  
**HMIS FLAMMABILITY:** 3  
**HMIS REACTIVITY:** 0  
**HMIS PROTECTION:** B

### 16. OTHER INFORMATION

N/A = Not Applicable; N/D = Not Determined

**DISCLAIMER:** To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards

are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.